



- | | |
|---|--|
| <p>Certifications • UL listed
• 5 Year limited warranty</p> <p>Power Size • Fixed power size 1,2, 3, 4 or 5
<i>See selection guide for details</i></p> <p>Body Material • Cast aluminum alloy, painted finish</p> <p>Mechanism • Hydraulic rack and pinion</p> <p>Fluid • Non-gumming, non-freezing hydraulic fluid</p> <p>Adjustments • Sweep speed valve
• Latching speed valve
• Cushioning backcheck valve – option</p> <p>Cover • Plastic pinion cap, painted finish</p> <p>Handing • Non-handed</p> | <p>Opening • 180° maximum</p> <p>Mounting • Tri-pack: regular¹, top jamb¹ or parallel arm²
• Maximum reveal: 3" (76mm)
• Drop plates – available
<i>(1) Arm shoe allows ±7.5% power adjustment
(2) May reduce spring power efficiency by 25%</i></p> <p>Hardware • Wood & machine screws
• Sex nuts & thru-bolts – available</p> <p>Available Arms • Regular arm</p> <p>Finish AL–Aluminum, painted; BP–Brass, painted; DU–Dark bronze, painted
<i>Other finishes available by special order</i></p> |
|---|--|

754	AL
MODEL	FINISH


SEE SELECTION GUIDE FOR DETAILS

SELECTION GUIDE

MODEL	POWER SIZE	WEIGHT CAPACITY ¹	MAX. DOOR WIDTH ²		BACKCHECK	DELAYED ACTION	FINISH	/CASE
			INTERIOR	EXTERIOR				
751	1	33–80 (15–36)	32 (813)	—	—	—	AL	10
752	2	55–100 (25–45)	36 (914)	—	—	—	AL	10
753	3	90–145 (40–66)	44 (1118)	—	—	—	AL, DU	10
754	4	125–190 (57–86)	48 (1219)	36 (914)	—	—	AL, DU	10
784					●	—	AL, DU	10
755	5	175–265 (80–120)	52 (1321)	44 (1118)	—	—	AL, BP, DU	10
785					●	—	AL	10

CAUTION: ANY DOOR CLOSER INSTALLED AND ADJUSTED BASED ON ADA REDUCED FORCE REQUIREMENTS MAY NOT RELIABLY CLOSE AND LATCH DOOR.

(1) WEIGHT CAPACITY RANGE IN POUNDS (KILOGRAMS) (2) MAXIMUM DOOR WIDTH IN INCHES (MILLIMETRES)



MODEL	A	B	C	D	E
751	¾ (19)	6½ (165)	1 ¹¹ / ₁₆ (43)	7 ⁷ / ₈ (181)	2 ⁹ / ₁₆ (65)
752/753	¾ (19)	8 ³ / ₁₆ (208)	1¾ (45)	8 ⁷ / ₈ (225)	2 ⁷ / ₈ (73)
754/755 (784/785)	¾ (19)	9 ¹ / ₁₆ (230)	1¾ (45)	9¾ (248)	2 ⁷ / ₈ (73)

IN (MM)

PARTS & ACCESSORIES



DP754
For parallel arm installations where the door top rail height is insufficient for direct mounting.
(Models 754 / 755).



SNB1420
Sex nut & thru-bolt kit (4) for doors 1¾" (44.5 mm) thick.



DPS740AL
Drop plate.



DPN740AL
Drop plate for narrow top rail.