

2295 SERIES

NARROW STILE EXIT DEVICE



Certifications • UL listed, Panic Exit
• 1 Year limited warranty

Rail Assembly • High strength aluminum
• Field sizable

Handing • Non-handed

Door Width • 30–38" (762–965 mm)
• 36–44" (914–1118 mm) –option

Door Thickness • 1 3/4" (45.5 mm)
Recommended for aluminum doors

Stile Width • 1 3/4" (44.5 mm) minimum
Measured from door edge

Projection • 2 1/16" (67 mm) from door surface

Latchbolt • Stainless steel

Strike • Steel, roller strike #2295S

Dogging • Hex key dogging

Hardware • Machine screws

Trims • Escutcheon trim – available
Sold separately, see 2295TE


Finish 20D–Dark bronze; 28–Aluminum
Other finishes available by special order

2295PR	3	–	28
MODEL	SIZE		FINISH

SELECTION GUIDE

MODEL	SIZE	DOOR WIDTH ¹	DOGGING	FINISH	/CASE	
2295PR	Panic Exit Hardware Rim Device	3	30-38 (762-965)	●	20D, 28	4
		4	36-44 (914-1118)			

(1) RECOMMENDED DOOR WIDTH, IN (MM), FOR NON-STANDARD SIZES OR INSTALLATIONS PLEASE CONTACT.



MODEL	A	B	C	D	E ¹	F	G	H	K	M
2295PR3	2 11/16 (67)	7 1/2 (191)	1 1/4 (32)	23 1/4 (591)	35 1/2 (902)	3 3/16 (81)	7 15/16 (201.6)	1 3/4 (44)	3/4 (19)	2 1/16 (52)
2295PR4					41 1/2 (1054)					

IN (MM) (1) CAN BE CUT TO SIZE - SEE PRODUCT INSTALLATION INSTRUCTIONS

2295TE ESCUTCHEON TRIM




Trim	2295TE70
Function	Entrance/Classroom
Finish	20D-Dark bronze, 28-Aluminum
Lever	Straight, no return
Cylinder ¹	1 1/4 (32) mortise
Door Thickness	1 3/4 (44.5)
Warranty	1 Year limited

IN (MM) (1) SOLID BRASS, 6-PIN CYLINDER, SCHLAGE "C", 2 KEYS INCLUDED - KEYING SERVICES AVAILABLE

PARTS & COMPONENTS



2295S
Standard roller strike.



2295AD
Dogging mechanism.