



TLA 421
Privacy with indicator



- Certifications**
- Conforms to ANSI/BHMA A156.5, Grade 2
 - UL listed, 3hr fire-rating*
 - 5 Year limited warranty
- (* Except privacy model 421)

- Door Thickness**
- 1 $\frac{3}{8}$ –1 $\frac{3}{4}$ " (35–44.5 mm)
 - SFIC Model: 1 $\frac{9}{16}$ –2" (40–51 mm)
 - Kit for 2 $\frac{1}{4}$ " (57 mm) – available

- Handing**
- Non handed

- Backset**
- 2 $\frac{3}{4}$ " (70 mm)
 - 2 $\frac{5}{8}$ " (60 mm) – available
 - 2 $\frac{3}{8}$ –2 $\frac{3}{4}$ " (60–70 mm) adjustable – available
 - 5" (127 mm) – available

- Deadbolt**
- Solid brass with hardened steel security pin
 - 1" (25.4 mm) throw

- Faceplate**
- Mortise type, square corners
 - 1 $\frac{1}{8}$ x2 $\frac{1}{4}$ " (29x57 mm)

- Strike**
- 2-piece security strike (wood/metal frame)
 - 1 $\frac{1}{8}$ x2 $\frac{3}{4}$ " (29x70 mm), square corners
 - Plastic dust-box

Other strikes available

- Chassis**
- Free-spinning cylinder collar
 - Steel cylinder housing
 - Exposed mounting screws

- Preparation**
- Cross bore: 1 $\frac{1}{2}$ or 2 $\frac{1}{8}$ " (38 mm or 54 mm)*
 - Edge bore: 1" (25.4 mm)
- (* 1 $\frac{1}{2}$ " (38 mm) installation will negate Grade 2 conformity, but will retain fire-rating.

- Cylinder**
- Solid brass, 6-pin
 - Schlage "C" keyway, 2 keys
 - Removable, rekeyable
 - Small format interchangeable core (SFIC) model – available

Other keyways and keying options available, including CX5 high security.

- Functions**
- 421 Privacy with indicator
 - 51 Single cylinder, thumb-turn
 - 60 Double cylinder

- Finish**
- 19–Matte black, 26D–Satin chrome,
 - 3–Polished brass, 32D–Satin stainless steel

Other finishes available by special order


TLA	51	-	32D	-U
SERIES	FUNCTION		FINISH	OPTION ⁽¹⁾

(1) OPTIONS: 238–2 3/8IN (60MM) BACKSET -U–ADJUSTABLE BACKSET

SELECTION GUIDE

SERIES	FUNCTION	FINISH ¹	/CASE
TLA	42I Privacy, with indicator*	26D, 32D	20
TLA	51 Single cylinder with thumb-turn ↔	19, 26D, 3, 32D	20
TLA	51-U Single cylinder with thumb-turn, adjustable backset option ↔	26D, 32D, 3	20
TLA	51IC Single cylinder with thumb-turn, SFIC (less core) ↔	26D, 32D	20
TLA	60 Double cylinder ↔	3, 32D	20

(1) OTHER FINISHES AND FUNCTIONS AVAILABLE, MINIMUM ORDER QUANTITIES AND/OR ADDITIONAL DELIVERY TIMES MAY BE REQUIRED
 ↔ KEYED FUNCTION; FULL KEYING SERVICES AVAILABLE (*) CANNOT ACCOMMODATE DOORS THICKER THAN 1-3/4IN (44.5 MM); NOT FIRE-RATED



	ø A	B	C
TLA	2 9/16 (65)	1 1/8 (29)	1 (25)
TLA 42I	2 9/16 (65)	1 1/32 (8.5)	1 (25)

IN (MM)

PARTS & ACCESSORIES



9111
Steel frame strike; square.
1 1/8 x 2 3/4" (29 x 70 mm)



9118
Wood frame strike; square.
1 1/8 x 2 3/4" (29 x 70 mm)

9118R
Wood frame strike; round.
1 1/8 x 2 3/4" (29 x 70 mm)



9806
CX5 high security SFIC core, 6 pin, 0 bitted

9807
CX5 high security SFIC core, 7 pin, 0 bitted

CX5-TPIC
Tailpiece for use with CX5 SFIC cores

CBI-BF7KD-26D
BEST® F type SFIC core, 7 pin, keyed different



TL007
Deadbolt: 2 3/8" (60 mm) backset,
1 x 2 1/4" (25.4 x 57 mm) faceplate

TL008
Deadbolt: 2 3/4" (70 mm) backset,
1 1/8 x 2 1/4" (28.5 x 57 mm) faceplate

TL009
Deadbolt: 5" (127 mm) backset,
1 x 2 1/4" (25.4 x 57 mm) faceplate
(not fire-rated)

TLA-LBU
Deadbolt: 2 3/8-2 3/4" (60-70 mm) adjustable
backset, 1 x 2 1/4" (25.4 x 57 mm) faceplate



TL020
Plastic spacer for latches with
1 x 2 1/4" (25.4 x 57 mm) faceplate



TLA85052
Longer spindle and screw kit for 2 1/4" (57 mm)
thick door. Cannot be used with TLA 42I
Indicator model.